

MAGNETOHYDRODYNAMIC RE-ENTRY SHIELDING

Kilometer-Scale Spacecraft Technical Feasibility Report

1. CONCEPT OVERVIEW

Traditional ablative or ceramic tile heat shields scale linearly with the surface area of a spacecraft. For a vessel measuring 1 kilometer in length, the mass penalty of a physical heat shield becomes prohibitive, severely limiting payload capacity. The proposed solution is an active **Magnetohydrodynamic (MHD) Heat Shield**.

During atmospheric re-entry, the immense friction and compression of atmospheric gases at hypersonic speeds (approx. 11 km/s) ionize the air, creating a superheated plasma envelope. Because plasma is electrically conductive, it responds to magnetic fields. By projecting a sufficiently powerful magnetic field ahead of the vessel, the bow shock and convective heat transfer can be deflected away from the physical hull.

Operating Principle

The system leverages a forward-mounted superconducting toroidal array to generate a magnetic "bubble". The Lorentz forces exerted on the incoming atmospheric plasma counteract the dynamic ram pressure, suspending the superheated plasma sheath at a safe standoff distance from the aerodynamic hull.




Figure 1.0: Simulated re-entry envelope and plasma deflection around a 1km vessel.

2. FIELD STRENGTH CALCULATIONS

To successfully deflect the incoming plasma, the magnetic pressure (P_m) exerted by the artificial field must equal or exceed the dynamic ram pressure (P_d) of the incoming atmosphere.

Step 1: Dynamic Pressure (P_d)

Assuming a peak re-entry velocity of $v = 11,000$ m/s and upper atmospheric density, the estimated peak

Step 3: Calculating Required Teslas (B)

Setting $P_m = P_d$:

$$10^6 = B^2 / (2 \times 1.257 \times 10^{-6})$$

3. GENERATOR ARCHITECTURE

Generating a 1.6 Tesla field over a volume large enough to encapsulate a 1 km starship requires an industrial-scale Superconducting Toroidal Coil Array. The system is mounted directly behind the forward nosecone to maximize the standoff distance of the bow shock.




Figure 2.0: Cutaway schematic of the forward-mounted Superconducting Toroidal Coil Array.



4. TECHNICAL SPECIFICATIONS

The power consumption during the critical re-entry window (approx. 180 seconds) is immense. The ship must route power from its primary fusion drives into high-current conversion modules to maintain the superconducting state and magnetic envelope under extreme thermal stress.

PARAMETER	VALUE	NOTES
Generator Topology	Superconducting Toroid	Liquid Helium (Cryogenic) cooled
Required Field Strength (<i>B</i>)	1.6 Teslas	Measured at 50m standoff from hull
Total Stored Magnetic Energy	~9.6 TeraJoules (TJ)	Inertial energy held within the coils
Nominal Re-entry Sequence	180 Seconds	Peak dynamic load duration
Sustained Electrical Power Load	1.0 GigaWatt (GW)	Includes active cryogenic cooling & losses
Total Consumed Energy	180 GigaJoules (GJ)	1.0 GW × 180s = 180 GJ
Field Shaping System	Asymmetric Coil Modulation	Adjusts envelope for pitch/yaw control

System Sub-Components

1. **Cryogenic Support Mandrel:** Houses the liquid helium loop required to keep the niobium-titanium (NbTi) or